

INTERSIL

# IM6402/IM6403 Universal Asynchronous Receiver Transmitter (UART)

## FEATURES

- Low Power — Less Than 10mW Typ. at 2MHz
- Operation Up to 4MHz Clock — IM6402A
- Programmable Word Length, Stop Bits and Parity
- Automatic Data Formatting and Status Generation
- Compatible with Industry Standard UART's — IM6402
- On-Chip Oscillator with External Crystal — IM6403
- Operating Voltage —
  - IM6402-1/03-1: 4-7V
  - IM6402A/03A: 4-11V
  - IM6402/03: 4-7V

## GENERAL DESCRIPTION

The IM6402 and IM6403 are CMOS/LSI UART's for interfacing computers or microprocessors to asynchronous serial data channels. The receiver converts serial start, data, parity and stop bits to parallel data verifying proper code transmission, parity, and stop bits. The transmitter converts parallel data into serial form and automatically adds start, parity, and stop bits.

The data word length can be 5, 6, 7 or 8 bits. Parity may be odd or even. Parity checking and generation can be inhibited. The stop bits may be one or two (or one and one-half when transmitting 5 bit code). Serial data format is shown in Figure 7.

The IM6402 and IM6403 can be used in a wide range of applications including modems, printers, peripherals and remote data acquisition systems. CMOS/LSI technology permits operating clock frequencies up to 4.0MHz (250K Baud) an improvement of 10 to 1 over previous PMOS UART designs. Power requirements, by comparison, are reduced from 670mW to 10mW. Status logic increases flexibility and simplifies the user interface.

The IM6402 differs from the IM6403 on pins 2, 17, 19, 22, and 40 as shown in Figure 5. The IM6403 utilizes pin 2 as a crystal divide control and pins 17 and 40 for an inexpensive crystal oscillator. TBREEmpty and DReady are always active. All other input and output functions of the IM6402 and IM6403 are identical.

## PIN CONFIGURATION

Vcc	1	40	EPE
GND	2	39	CLS1
RDR	3	38	CLS2
RBR	4	37	SBS
RBR	5	36	PI
RBR	6	35	CRL
RBR	7	34	TBR8
RBR	8	33	TBR7
RBR	9	32	TBR6
RBR	10	31	TBR5
RBR	11	30	TBR4
RBR	12	29	TBR3
PE	13	28	TBR2
FE	14	27	TBR1
OE	15	26	TRO
SFD	16	25	TRE
DRR	17	24	TRE
DRR	18	23	TRE
DRR	19	22	TRE
RRR	20	21	MR



TABLE 1

PIN	IM6402	IM6403 w/XTAL	IM6403 w/EXT CLOCK
2	N/C	DIVIDE CONTROL	DIVIDE CONTROL
17	RRC	XTAL	EXTERNAL CLOCK INPUT
40	TRC	XTAL	GND

## ORDERING INFORMATION

ORDER CODE	IM6402-1/03-1	IM6402A/03A	IM6402/03
PLASTIC PKG	IM6402-1/03-1PL	IM6402/03-AIPL	IM6402/03-IPL
CERAMIC PKG	IM6402-1/03-1IDL	IM6402/03-AIDL	—
MILITARY TEMP.	IM6402-1/03-1MDL	IM6402/03-AMDL	—
MILITARY TEMP. WITH 883B	IM6402-1/03-1MDL/883B	IM6402/03-AMDL/883B	—

## PACKAGE DIMENSIONS



# IM6403 Asynchronous Transmitter (UART)


## FUNCTION

are CMOS/LSI UART's for microprocessors to asynchronous. The transmitter converts serial start, data, and automatically adds start, 6, 7 or 8 bits. Parity may be odd generation can be inhibited. The serial data format is shown in


can be used in a wide range of systems, printers, peripherals and CMOS/LSI technology frequencies up to 4.0MHz (250K Baud) or previous PMOS UART designs. Comparison, are reduced from logic increases flexibility and

IM6403 on pins 2, 17, 19, 22, and IM6403 utilizes pin 2 as a crystal and 40 for an inexpensive crystal. All other of the IM6402 and IM6403 are

## MECHANICAL



## IM6402/IM6403



\*DIFFERS BETWEEN IM6402 AND IM6403.

FIGURE 1. Pin Configuration

## IM6403 FUNCTIONAL PIN DEFINITION

PIN	SYMBOL	DESCRIPTION
1	V <sub>CC</sub>	Positive Power Supply
2	IM6402-N/C IM6403-Control	No Connection Divide Control High: 2 <sup>4</sup> (16) Divider Low: 2 <sup>11</sup> (2048) Divider
3	GND	Ground
4	RRD	A high level on RECEIVER REGISTER DISABLE forces the receiver holding register outputs RBR1-RBR8 to a high impedance state.
5	RBR8	The contents of the RECEIVER BUFFER REGISTER appear on these three-state outputs. Word formats less than 8 characters are right justified to RBR1.
6	RBR7	See Pin 5 — RBR8
7	RBR6	See Pin 5 — RBR8
8	RBR5	See Pin 5 — RBR8
9	RBR4	See Pin 5 — RBR8
10	RBR3	See Pin 5 — RBR8
11	RBR2	See Pin 5 — RBR8
12	RBR1	See Pin 5 — RBR8
13	PE	A high level on PARITY ERROR indicates that the received parity does not match parity programmed by control bits. The output is active until parity matches on a succeeding character. When parity is inhibited, this output is low.

## IM6403 FUNCTIONAL PIN DEFINITION (Continued)

PIN	SYMBOL	DESCRIPTION
14	FE	A high level on FRAMING ERROR indicates the first stop bit was invalid. FE will stay active until the next valid character's stop bit is received.
15	OE	A high level on OVERRUN ERROR indicates the data received flag was not cleared before the last character was transferred to the receiver buffer register. The Error is reset at the next character's stop bit if DRR has been performed (i.e., DRR: active low).
16	SFD	A high level on STATUS FLAGS DISABLE forces the outputs PE, FE, OE, DR, TBRE to a high impedance state. See Figure 4 and Figure 5. *IM6402 only.
17	IM6402-RRC IM6403-XTAL or EXT CLK IN	The RECEIVER REGISTER CLOCK is 16X the receiver data rate.
18	DRR	A low level on DATA RECEIVED RESET clears the data received output (DR), to a low level.
19	DR	A high level on DATA RECEIVED indicates a character has been received and transferred to the receiver buffer register.
20	RRI	Serial data on RECEIVER REGISTER INPUT is clocked into the receiver register.
21	MR	A high level on MASTER RESET (MR) clears PE, FE, OE, DR, TRE and sets TBRE, TRO high. Less than 18 clocks after MR goes low, TRE returns high. MR does not clear the receiver buffer register, and is required after power-up.
22	TBRE	A high level on TRANSMITTER BUFFER REGISTER EMPTY indicates the transmitter buffer register has transferred its data to the transmitter register and is ready for new data.
23	TBRL	A low level on TRANSMITTER BUFFER REGISTER LOAD transfers data from inputs TBR1-TBR8 into the transmitter buffer register. A low to high transition on TBRL requests data transfer to the transmitter register. If the transmitter register is busy, transfer is automatically delayed so that the two characters are transmitted end to end. See Figure 2.
24	TRE	A high level on TRANSMITTER REGISTER EMPTY indicates completed transmission of a character including stop bits.
25	TRO	Character data, start data and stop bits appear serially at the TRANSMITTER REGISTER OUTPUT.



# IM6402/IM6403

## IM6403 FUNCTIONAL PIN DEFINITION (Continued)

PIN	SYMBOL	DESCRIPTION
26	TBR1	Character data is loaded into the TRANSMITTER BUFFER REGISTER via inputs TBR1-TBR8. For character formats less than 8-bits, the TBR8, 7, and 6 inputs are ignored corresponding to the programmed word length.
27	TBR2	See Pin 26 — TBR1
28	TBR3	See Pin 26 — TBR1
29	TBR4	See Pin 26 — TBR1
30	TBR5	See Pin 26 — TBR1
31	TBR6	See Pin 26 — TBR1
32	TBR7	See Pin 26 — TBR1
33	TBR8	See Pin 26 — TBR1
34	CRL	A high level on CONTROL REGISTER LOAD loads the control register. See Figure 3.

# INTERSIL

## IM6403 FUNCTIONAL PIN DEFINITION (Continued)

PIN	SYMBOL	DESCRIPTION
35	PI*	A high level on PARITY INHIBIT inhibits parity generation, parity checking and forces PE output low.
36	SBS*	A high level on STOP BIT SELECT selects 1.5 stop bits for a 5 character format and 2 stop bits for other lengths.
37	CLS2*	These inputs program the CHARACTER LENGTH SELECTED. (CLS1 low CLS2 low 5-bits) (CLS1 high CLS2 low 6-bits) (CLS1 low CLS2 high 7-bits) (CLS1 high CLS2 high 8-bits)
38	CLS1*	See Pin 37 — CLS2
39	EPE*	When PI is low, a high level on EVEN PARITY ENABLE generates and checks even parity. A low level selects odd parity.
40	IM6402-TRC IM6403-XTAL or GND	The TRANSMITTER REGISTER CLOCK is 16X the transmit data rate.

\*See Table 2 (Control Word Function)

TABLE 2. Control Word Function

CONTROL WORD					DATA BITS	PARITY BIT	STOP BIT(S)
CLS2	CLS1	PI	EPE	SBS			
L	L	L	L	L	5	ODD	1
L	L	L	L	H	5	ODD	1.5
L	L	L	H	L	5	EVEN	1
L	L	L	H	H	5	EVEN	1.5
L	L	H	X	L	5	DISABLED	1
L	L	H	X	H	5	DISABLED	1.5
L	H	L	L	L	6	ODD	1
L	H	L	L	H	6	ODD	2
L	H	L	H	L	6	EVEN	1
L	H	L	H	H	6	EVEN	2
L	H	H	X	L	6	DISABLED	1
L	H	H	X	H	6	DISABLED	2
H	L	L	L	L	7	ODD	1
H	L	L	L	H	7	ODD	2
H	L	L	H	L	7	EVEN	1
H	L	L	H	H	7	EVEN	2
H	L	H	X	L	7	DISABLED	1
H	L	H	X	H	7	DISABLED	2
H	H	L	L	L	8	ODD	1
H	H	L	L	H	8	ODD	2
H	H	L	H	L	8	EVEN	1
H	H	L	H	H	8	EVEN	2
H	H	H	X	L	8	DISABLED	1
H	H	H	X	H	8	DISABLED	2

X = Don't Care

# IM6402/IM6403

## ABSOLUTE MAXIMUMS

Operating Temperature  
Industrial IM6402AI/O  
Military IM6402AM/O  
Storage Temperature  
Operating Voltage  
Supply Voltage  
Voltage On Any Input or

## D.C. CHARACTERISTICS TEST CONDITIONS:

	SYMBOL	
1	V <sub>IH</sub>	Input V
2	V <sub>IL</sub>	Input V
3	I <sub>IL</sub>	Input L
4	V <sub>OH</sub>	Output
5	V <sub>OL</sub>	Output
6	I <sub>OL</sub>	Output
7	I <sub>CC</sub>	Power S
8	I <sub>CC</sub>	Power S
9	I <sub>CC</sub>	Power S
10	C <sub>IN</sub>	Input C
11	C <sub>O</sub>	Output I

NOTE 1: Except IM6403 XTAL  
NOTE 2: V<sub>CC</sub> = 5V, T<sub>A</sub> = 25

## A.C. CHARACTERISTICS TEST CONDITIONS: V

	SYMBOL	
1	f <sub>C</sub>	Clock Fr
2	f <sub>CRYSTAL</sub>	Crystal F
3	t <sub>PW</sub>	Pulse Wic
4	t <sub>MR</sub>	Pulse Wic
5	t <sub>DS</sub>	Input Da
6	t <sub>DH</sub>	Input Da
7	t <sub>EN</sub>	Output E

## TIMING DIAGRAMS




FIGURE 2. Data Input

# IM6402/IM6403

## IM6402A/IM6403A

INTERSIL

### ABSOLUTE MAXIMUM RATINGS

Operating Temperature	
Industrial IM6402AI/03AI	-40°C to +85°C
Military IM6402AM/03AM	-55°C to +125°C
Storage Temperature	-65°C to 150°C
Operating Voltage	4.0V to 11.0V
Supply Voltage	+12.0V
Voltage On Any Input or Output Pin	-0.3V to $V_{CC} + 0.3V$

NOTE: Stresses above those listed under "Absolute Maximum Ratings" may cause permanent device failure. These are stress ratings only and functional operation of the devices at these or any other conditions above those indicated in the operation sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may cause device failures.

### C. CHARACTERISTICS

TEST CONDITIONS:  $V_{CC} = 4V$  to  $11V$ ,  $T_A =$  Industrial or Military

	SYMBOL	PARAMETER	CONDITIONS	MIN	TYP <sup>2</sup>	MAX	UNITS
1	$V_{IH}$	Input Voltage High		70% $V_{CC}$			V
2	$V_{IL}$	Input Voltage Low				20% $V_{CC}$	V
3	$I_{IL}$	Input Leakage[1]	$GND \leq V_{IN} \leq V_{CC}$	-1.0		1.0	$\mu A$
4	$V_{OH}$	Output Voltage High	$I_{OH} = 0mA$	$V_{CC} - 0.01$			V
5	$V_{OL}$	Output Voltage Low	$I_{OL} = 0mA$			$GND + 0.01$	V
6	$I_{OL}$	Output Leakage	$GND \leq V_{OUT} \leq V_{CC}$	-1.0		1.0	$\mu A$
7	$I_{CC}$	Power Supply Current Standby	$V_{IN} = GND$ or $V_{CC}$		5.0	500	$\mu A$
8		Power Supply Current IM6402A Dynamic	$f_C = 4MHz$			9.0	mA
9	$I_{CC}$	Power Supply Current IM6403A Dynamic	$f_{CRYSTAL} = 3.58MHz$			13.0	mA
10	$C_{IN}$	Input Capacitance[1]			7.0	8.0	pF
11	$C_O$	Output Capacitance[1]			8.0	10.0	pF

NOTE 1: Except IM6403 XTAL input pins (i.e. pins 17 and 40).

NOTE 2:  $V_{CC} = 5V$ ,  $T_A = 25^\circ C$ .

### C. CHARACTERISTICS

TEST CONDITIONS:  $V_{CC} = 10V \pm 5\%$ ,  $C_L = 50pF$ ,  $T_A =$  Industrial or Military

	SYMBOL	PARAMETER	CONDITIONS	MIN	TYP <sup>2</sup>	MAX	UNITS
1	$f_C$	Clock Frequency IM6402A		D.C.	6.0	4.0	MHz
2	$f_{CRYSTAL}$	Crystal Frequency IM6403A			8.0	6.0	MHz
3	$tpw$	Pulse Widths CRL, DRR, TBRL		100	40		ns
4	$t_{MR}$	Pulse Width MR		400	200		ns
5	$t_{DS}$	Input Data Setup Time	See Timing Diagrams (Figures 2,3,4)	40	0		ns
6	$t_{DH}$	Input Data Hold Time		30	30		ns
7	$t_{EN}$	Output Enable Time			40	70	ns

### TIMING DIAGRAMS




FIGURE 2. Data Input Cycle




FIGURE 3. Control Register Load Cycle




FIGURE 4. Status Flag Enable Time or Data Output Enable Time



# IM6402/IM6403 IM6402-1/IM6403-1

## ABSOLUTE MAXIMUM RATINGS

Operating Temperature	
Industrial IM6402-11/03-11	-40°C to +85°C
Military IM6402-1M/03-1M	-55°C to +125°C
Storage Temperature	-65°C to +150°C
Operating Voltage	4.0V to 7.0V
Supply Voltage	+8.0V
Voltage On Any Input or Output Pin	-0.3V to V <sub>CC</sub> +0.3V

## D.C. CHARACTERISTICS

TEST CONDITIONS: V<sub>CC</sub> = 5.0 ± 10%, T<sub>A</sub> = Industrial or Military

	SYMBOL	PARAMETER	CONDITIONS	MIN	TYP <sup>2</sup>	MAX	UNITS
1	V <sub>IH</sub>	Input Voltage High		V <sub>CC</sub> -2.0			V
2	V <sub>IL</sub>	Input Voltage Low				0.8	V
3	I <sub>IL</sub>	Input Leakage[1]	GND < V <sub>IN</sub> < V <sub>CC</sub>	-1.0		1.0	μA
4	V <sub>OH</sub>	Output Voltage High	I <sub>OH</sub> = -0.2mA	2.4			V
5	V <sub>OL</sub>	Output Voltage Low	I <sub>OL</sub> = 2.0mA			0.45	V
6	I <sub>OL</sub>	Output Leakage	GND < V <sub>OUT</sub> < V <sub>CC</sub>	-1.0		1.0	μA
7	I <sub>CC</sub>	Power Supply Current Standby	V <sub>IN</sub> =GND or V <sub>CC</sub>		1.0	100	μA
8	I <sub>CC</sub>	Power Supply Current IM6402 Dynamic	f <sub>C</sub> = 2MHz			1.9	mA
9	I <sub>CC</sub>	Power Supply Current IM6403 Dynamic	f <sub>CRYSTAL</sub> =3.58MHz			5.5	mA
10	C <sub>IN</sub>	Input Capacitance[1]			7.0	8.0	pF
11	C <sub>O</sub>	Output Capacitance[1]			8.0	10.0	pF

NOTE 1: Except IM6403 XTAL input pins (i.e. pins 17 and 40).

NOTE 2: V<sub>CC</sub> = 5V, T<sub>A</sub> = 25°C.

## A.C. CHARACTERISTICS

TEST CONDITIONS: V<sub>CC</sub> = 5.0V ± 10%, C<sub>L</sub> = 50pF, T<sub>A</sub> = Industrial or Military

	SYMBOL	PARAMETER	CONDITIONS	MIN	TYP <sup>2</sup>	MAX	UNITS
1	f <sub>C</sub>	Clock Frequency IM6402		D.C.	3.0	2.0	MHz
2	f <sub>CRYSTAL</sub>	Crystal Frequency IM6403			4.0	3.58	MHz
3	t <sub>PW</sub>	Pulse Widths CRL, DRR, TBRL		150	50		ns
4	t <sub>MR</sub>	Pulse Width MR	See Timing Diagrams (Figures 2,3,4)	400	200		ns
5	t <sub>DS</sub>	Input Data Setup Time		50	20		ns
6	t <sub>DH</sub>	Input Data Hold Time		60	40		ns
7	t <sub>EN</sub>	Output Enable Time			80	160	ns




FIGURE 5. Functional Difference Between IM6402 and IM6403 UART (6403 has On-Chip 4/11 Stage Divider)

The IM6403 differs from the IM6402 on three inputs (RRC, TRC, pin 2) as shown in Figure 5. Two outputs (TBRE, DR) are not three-state as on the IM6402, but are always active. The on-chip divider and oscillator allow an inexpensive crystal to be used as a timing source rather than additional circuitry such

as baud rate generators. For example, a color TV crystal at 3.579545MHz results in a baud rate of 109.2Hz for an easy teletype interface (Figure 11). A 9600 baud interface may be implemented using a 2.4576MHz crystal with the divider set to divide by 16.

# IM6402/IM6403 IM6402/IM6403

## ABSOLUTE MAXIMUM RATINGS

Operating Temperature	
IM6402/03	
Storage Temperature	
Operating Voltage	
Supply Voltage	
Voltage On Any Input or Output Pin	

## D.C. CHARACTERISTICS

TEST CONDITIONS: V<sub>CC</sub>

	SYMBOL	PARAMETER
1	V <sub>IH</sub>	Input Voltage High
2	V <sub>IL</sub>	Input Voltage Low
3	I <sub>IL</sub>	Input Leakage
4	V <sub>OH</sub>	Output Voltage High
5	V <sub>OL</sub>	Output Voltage Low
6	I <sub>OL</sub>	Output Leakage
7	I <sub>CC</sub>	Power Supply Current Standby
8	I <sub>CC</sub>	Power Supply Current IM6402 Dynamic
9	I <sub>CC</sub>	Power Supply Current IM6403 Dynamic
10	C <sub>IN</sub>	Input Capacitance
11	C <sub>O</sub>	Output Capacitance


NOTE 1: Except IM6403 XTAL input pins (i.e. pins 17 and 40).

NOTE 2: V<sub>CC</sub> = 5V, T<sub>A</sub> = 25°C.

## A.C. CHARACTERISTICS

TEST CONDITIONS: V<sub>CC</sub>

	SYMBOL	PARAMETER
1	f <sub>C</sub>	Clock Frequency
2	f <sub>CRYSTAL</sub>	Crystal Frequency
3	t <sub>PW</sub>	Pulse Widths
4	t <sub>MR</sub>	Pulse Width MR
5	t <sub>DS</sub>	Input Data Setup Time
6	t <sub>DH</sub>	Input Data Hold Time
7	t <sub>EN</sub>	Output Enable Time



# IM6402/IM6403

IM6402/IM6403

## ABSOLUTE MAXIMUM RATINGS

Operating Temperature	-40°C to +85°C
Storage Temperature	-65°C to 150°C
Operating Voltage	4.0V to 7.0V
Supply Voltage	+8.0V
Voltage On Any Input or Output Pin	-0.3V to $V_{CC} + 0.3V$

## C. CHARACTERISTICS

TEST CONDITIONS:  $V_{CC} = 5.0 \pm 10\%$ ,  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$

	SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
1	$V_{IH}$	Input Voltage High		$V_{CC}-2.0$			V
2	$V_{IL}$	Input Voltage Low				0.8	V
3	$I_{IL}$	Input Leakage[1]	$GND \leq V_{IN} \leq V_{CC}$	-5.0		5.0	$\mu\text{A}$
4	$V_{OH}$	Output Voltage High	$I_{OH} = -0.2\text{mA}$	2.4			V
5	$V_{OL}$	Output Voltage Low	$I_{OL} = 1.6\text{mA}$			0.45	V
6	$I_{OL}$	Output Leakage	$GND \leq V_{OUT} \leq V_{CC}$	-5.0		5.0	$\mu\text{A}$
7	$I_{CC}$	Power Supply Current Standby	$V_{IN} = GND$ or $V_{CC}$		1.0	800	$\mu\text{A}$
8	$I_{CC}$	Power Supply Current IM6402 Dynamic	$f_C = 500\text{KHz}$			1.2	mA
9	$I_{CC}$	Power Supply Current IM6403 Dynamic	$f_{CRYSTAL} = 2.46\text{MHz}$			3.7	mA
10	$C_{IN}$	Input Capacitance[1]			7.0	8.0	pF
11	$C_O$	Output Capacitance[1]			8.0	10.0	pF

NOTE 1: Except IM6403 XTAL input pins (i.e. pins 17 and 40).

NOTE 2:  $V_{CC} = 5V$ ,  $T_A = 25^\circ\text{C}$ .

## C. CHARACTERISTICS

TEST CONDITIONS:  $V_{CC} = 5.0V \pm 10\%$ ,  $C_L = 50\text{pF}$ ,  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$

	SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
1		Clock Frequency IM6402		D.C.	3.0	1.0	MHz
2	$f_{CRYSTAL}$	Crystal Frequency IM6403			4.0	2.46	MHz
3	$t_{PW}$	Pulse Widths CRL, DRR, TBRL		225	50		ns
4	$t_{MR}$	Pulse Width MR	See Timing Diagrams (Figures 2,3,4)	600	200		ns
5	$t_{DS}$	Input Data Setup Time		75	20		ns
6	$t_{DH}$	Input Data Hold Time		90	40		ns
7	$t_{EN}$	Output Enable Time			80	190	ns




FIGURE 6. IM6402/03 Functional Block Diagram



## M6402/IM6403

### TRANSMITTER OPERATION

The transmitter section accepts parallel data, formats it and transmits it in serial form (Figure 7) on the TROutput terminal.




FIGURE 7. Serial Data Format

Transmitter timing is shown in Figure 8. (A) Data is loaded into the transmitter buffer register from the inputs TBR1 through TBR8 by a logic low on the TBRLoad input. Valid data must be present at least  $t_{DS}$  prior to and  $t_{OH}$  following the rising edge of TBRLoad. If words less than 8 bits are used, only the least significant bits are used. The character is right justified into the least significant bit, TBR1. (B) The rising edge of TBRLoad clears TBREmpty. 0 to 1 clock cycles later data is transferred to the transmitter register and TREmpty is cleared and transmission starts. TBREmpty is reset to a logic high. Output data is clocked by TRClock. The clock rate is 16 times the data rate. (C) A second pulse on TBRLoad loads data into the transmitter buffer register. Data transfer to the transmitter register is delayed until transmission of the current character is complete. (D) Data is automatically transferred to the transmitter register and transmission of that character begins.




FIGURE 8. Transmitter Timing (Not to Scale)

### RECEIVER OPERATION

Data is received in serial form at the RI input. When no data is being received, RI input must remain high. The data is clocked through the RRClock. The clock rate is 16 times the data rate. Receiver timing is shown in Figure 9.

(A) A low level on DRReset clears the DReady line. (B) During the first stop bit data is transferred from the receiver register to the RBRegister. If the word is less than 8 bits, the unused most significant bits will be a logic low. The output character is right justified to the least significant bit RBR1. A logic high on OError indicates overruns. An overrun occurs when DReady has not been cleared before the present character was transferred to the RBRegister. A logic high on PError indicates a parity error. (C) 1/2 clock cycle later DReady is set to a logic high and FError is evaluated. A logic high on FError indicates an invalid stop bit was received. The receiver will not begin searching for the next start bit until a stop bit is received.




FIGURE 9. Receiver Timing (Not to Scale)

### START BIT DETECTION

The receiver uses a 16X clock for timing (see Figure 10.) The start bit (A) could have occurred as much as one clock cycle before it was detected, as indicated by the shaded portion. The center of the start bit is defined as clock count 7 1/2. If the receiver clock is a symmetrical square wave, the center of the start bit will be located within  $\pm 1/2$  clock cycle,  $\pm 1/32$  bit or  $\pm 3.125\%$ . The receiver begins searching for the next start bit at the center of the first stop bit.




FIGURE 10. Start Bit Timing

### TYPICAL APPLICATION

Microprocessor systems, which are inherently parallel in nature, often require an asynchronous serial interface. This function can be performed easily with the IM6402/03 UART. Figure 11 shows how the IM6403 can be interfaced to an IM6100 microcomputer system with the aid of an IM6101 Programmable Interface Element (PIE). The PIE interprets Input/Output transfer (IOT) instructions from the processor and generates read and write pulses to the UART. The SENSE lines on the PIE are also employed to allow the processor to detect UART status. In particular, the processor must know when the Receive Buffer Register has accumulated a character (DR active), and when the Transmit Buffer Register can accept another character to be transmitted.

In this example the characters to be received or transmitted will be eight bits long (CLS 1 and 2: both HIGH) and transmitted with no parity (PI:HIGH) and two stop bits (SBS:HIGH). Since these control bits will not be changed during operation, Control Register Load (CRL) can be tied high. Remember, since the IM6402/03 is a CMOS device, all unused inputs should be committed.


The baud rate at which the transmitter and receiver will operate is determined by the external crystal and DIVIDE CONTROL pin on the IM6403. The internal divider can be set to reduce the crystal frequency by either 16 (PIN 2:HIGH) or 2048 (PIN 2:LOW) times. The frequency out of the internal divider

## IM6402/IM64

should be 16 times the desired baud, this example will use a and DIVIDE CONTROL set low receive (RRC) and transmit (T

To assure consistent and correct operation, the processor must be reset after power-up active high, and could be driven through still another inverter. The processor and R-C network rising capacitor voltage does not pulse after power-up (~100ms) assure that the on-board crystal starts.

The IM6402 supports the processor quite easily by tying the TBR command from the processor BUFFER REGISTER onto the REGISTER DISABLE (RRD) pin. The processor clocks data from the BUFFER REGISTER using TBR



should be 16 times the desired baud rate. To generate 110 baud, this example will use a 3.579545MHz color TV crystal and DIVIDE CONTROL set low. The IM6402 may use different receive (RRC) and transmit (TRC) clock rates, but requires an external clock generator.

To assure consistent and correct operation, the IM6402/03 must be reset after power-up. The Master Reset (MR) pin is active high, and could be driven reliably from a Schmitt trigger inverter and R-C delay. In this example, the IM6100 is reset through still another inverter. The Schmitt trigger between the processor and R-C network is needed to assure that a slow rising capacitor voltage does not re-trigger RESET. A long reset pulse after power-up (~100ms) is required by the processor to assure that the on-board crystal oscillator has sufficient time to start.

The IM6402 supports the processor's bi-directional data bus quite easily by tying the TBR and RBR buses together. A read command from the processor will enable the RECEIVER BUFFER REGISTER onto the bus by using the RECEIVER REGISTER DISABLE (RRD) pin. A write command from the processor clocks data from the bus into the TRANSMITTER BUFFER REGISTER using TBRL. Figure 11 shows a NAND gate

driving TBRL from the WRITE<sub>2</sub> pin on the PIE. This gate is used to generate a rising edge to TBRL at the point where data is stable on the bus, and to hold TBRL high until the UART actually transfers the data to its internal buffer. If TBRL were allowed to return low before TBRE went high, the intended output data would be overwritten, since the TBR is a transparent latch.

Although not shown in this example, the error flags (PE, FE, OE) could be read by the processor using the other READ line from the PIE. Since an IM6403 is used, TBRE and DR are not affected by the STATUS FLAGS DISABLE pin. Thus, the three error flags can be tied to the data bus and gated by connecting SFD to READ<sub>2</sub>.

If parity is not inhibited, a parity error will cause the PE pin to go high until the next valid character is received.

A framing error is generated when an expected stop bit is not received. FE will stay high after the error until the next complete character's stop bit is received.

The overrun error flag is set if a received character is transferred to the RECEIVER BUFFER REGISTER when the previous character has not been read. The OE pin will stay high until the next received stop bit after a DRR is performed.




FIGURE 11. 110 Baud Serial Interface for IM6100 System